ALEWOOD

SOUTH AFRICA

Halewood International South Africa (Pty) Ltd 1/a Halewood Company Registration number 1998/001887/07 ood South Africa

www.halewood.co.za

INVOICE TO:

PROMOTIONAL STOCK - ZUKISANI

DELIVER TO:

PROMOTIONAL:STOCK - ZUKISANI LUYENGE

LUYENGE

PR0367 CUST ACC

A-Blackhorse outlets CUSTOMER REF

STORE NO.

OUR REF 1972980

ORD DATE 03/12/24

INV DATE 04/12/24

30 Days

PM BR

Z REP

61 TORONTO STREET BENONI 1501 APEX EXTENSION 1

PO BOX 2132

SOUTH AFRICA **BENONI 1500**

> FAX: +27 11 422 5888 TEL: +27 11 746 4200

FIRST NATIONAL BANK BANKING DETAILS:

BRANCH CODE: 240129 A/C NO: 62889748368

REFERENCE: PRO367

VAT Reg No: 4590177624

MANUFACTURING & DISTRIBUTION LICENCE: RG000275

Printed on:

10:35.49

04/12/2024

at:

1891274

Shipping Instructions: TERMS GA 円 Supplier Copy Tax Invoice CUST VAT NUM

Stock Code	Description C/TWIST WATERMELON 440ML	Pack CS	Cases	Bottles 0	HS Wh	Unit Price 0.00
CTPWATERMELON440ML RSPINECRUSH440ML	C/TWIST WATERMELON 440ML RED SQ PINE CRUSH 440ML	C CS	6 6	0 0	ቼ ቼ	
	JACSOO CO					

PAYMENT TERMS STRICTLY C.O.D. UNLESS CREDIT TERMS HAVE BEEN ARRANGED IN WRITING

TRANSPORTATION:

PLEASE RECEIVE ABOVE GOODS IN GOOD ORDER & CONDITION
PLEASE RECEIVE ABOVE GOODS and those detailed in this Waybill should be immediately notified
Any discrepancy between goods received and those detailed in this Waybill should be immediately notified
No responsibility accepted for goods signed for unchected.

Any discrepanyly between goods received and those detailed in this Waybill should be immediately notified No responsibility appealed for goods signed for unchecked

arrangements are made in writing

VAT

ZAR

0.00 0.00

TOTAL

PLEASE RECEIVE ABOVE GOODS IN GOOD ORDER & CONDITION

16

0

SUB-TOTAL

ZAR

0.00

goods may be returned unless prior arrangements are made in writing turns are subject to a 10% handling charge ercial quality equipment is not to be used for lifting applications

SIGNATURE

VEHICLE REGISTRATION No:

PRINT NAME

DATE

SIGNATURE

DATE

PRINT NAME

1000

rat is not to be used for lifting applications

Page 1 of 1